



You want easy. You want fast. You want great images.

Kodak i30 and i40 Scanners



Get everything you want from a small desktop scanner – and more.

- Simplex / Duplex Scanner with 50 page ADF
- Up to 25 pages – or 50 images (Duplex) – per minute in Bitonal and Colour
- NEW** • Unique special document feeder on the i40 model for front-feed, front-return scanning of small or thick documents
- NEW** • Easily select up to nine assigned scanning applications (such as KODAK Capture Software) at the touch of a button
- PerfectPage Image Processing built in – Renowned image quality from Kodak
- Robust suite of bundled software including Scan-to-PDF with OCR
- USB 2.0 interface – card and cable included
- Easy setup and integration
- Fits in any work space



KODAK Capture
Software Lite




Features and Benefits

Perfect Page with iThresholding: Advanced image processing from Kodak that allows you to scan even poor-quality documents at full speed and get exceptional images. Boosts productivity by virtually eliminating the need to rescan or change settings.



Competitive scanner



Perfect Page Scanning with iThresholding, only from Kodak

Automatic image cropping and straightening for outstanding image accuracy at full scanning speed.

Fast scanning: Up to 25 pages or 50 images per minute.

Five output options: Colour, bitonal, greyscale, simultaneous bitonal and greyscale and simultaneous bitonal and colour.

One-button functionality: Allows you to assign up to nine scanning applications* and select one at the touch of a button. Then, just press the scanner's Start button to begin scanning with the selected application. (*application support required)

Feature-rich bundled software makes it easy to maximize productivity right out of the box.

- KODAK Capture Software, Lite, installs in minutes and offers a range of scanning features for practically any workgroup application. Easily upgradeable to the full version of Capture Software.
- READIRIS Pro Corporate Edition provides key functions for locating textual information fast, including multi-page optical character recognition (OCR) and direct scanning to searchable PDF files.

For integrators, bundled ISIS and Kodak-developed TWAIN drivers deliver speedy system integration. For end-users, the exclusive, Kodak-developed TWAIN drivers enable Kodak's advanced image processing at the scanner's full rated speed.

Brightness and contrast control: Customize colour output to fit your application.

VRS compatible for more imaging options.

Flexible Electronic Colour Dropout: Suppress non-critical red, green or blue background to improve forms processing.

Reliable multi-feed detection for better scanning productivity.

Quiet operation and small footprint: The i30 and i40 models fit easily on any desktop.

KODAK Service & Support: The Scanners come with a one year European warranty with advanced unit replacement and 4-day response time as standard. Customers have the option to upgrade to a 3-year warranty with next-business day response.

Special Document Feeder (i40 only): New application opportunities for transaction scanning with new front feeding and ejecting function! This unique feeder makes it easy to scan small and/or thick documents such as identification cards, licenses, and insurance and medical cards. For easy access, it attaches or detaches in seconds, and features front-feeding and return of documents.



Specifications

Recommended Daily Volume	Up to 1,000 pages per day
Throughput Speeds (portrait, A4) ppm = pages/minute (simplex) ipm = images/minute (duplex)	Bitonal/Greyscale: Up to 25 ppm/50 ipm @ 200dpi Colour: Up to 25 ppm/50 ipm @ 150 dpi Up to 25 ppm/40 ipm @ 200 dpi
Scanning Technology	i30: Single CCD i40: Dual CCD Greyscale output bit depth is 256 levels (8-bit) Colour capture bit depth is 48 bits (16 x 3) Colour output bit depth is 24 bits (8 x 3)
Optical Resolution	600 dpi
Illumination	Fluorescent (cold cathode)
Output Resolution	75, 100, 150, 200, 240, 300, 400 and 600 dpi
Maximum Document Size	215 mm x 355.6 mm
Minimum Document Size	Single-sheet feeding: 50 mm x 87.5 mm Multiple-sheet feeding: 87.5 mm x 125 mm
Paper Thickness and Weight	52-105 g/m ² paper; special document feeder supports a wider range
Feeder s	ADF: Up to 50 sheets of 75 g/m ² paper; special document feeder for front-feed, front-return single document scanning
Multi-feed Detection	Length detection
Connectivity	USB 2.0 (card and cable included)
Bundled Software	TWAIN and ISIS drivers; KODAK Capture Software, Lite; READIRIS Pro Corporate Edition
Imaging Features (in the scanner)	Perfect Page Scanning with iThresholding, Adaptive Threshold Processing, Deskew, Autocrop, Relative Cropping, Aggressive Cropping, Electronic Colour Dropout, Simultaneous output of bitonal and colour or bitonal and greyscale images, colour processing tables
File Format Outputs	BMP, TIFF and JPEG (searchable PDF with bundled software)
Electrical Requirements	100-240 V (International); 50-60 Hz
Power Consumption	i30 Standby: <12 Watts; i30 Running: <30 Watts i40 Standby: <12 Watts; i40 Running: <40 Watts
Environmental Factors	ENERGY STAR qualified scanners Operating temperature: 10-35° C Operating humidity: 10% to 85% RH
Acoustical Noise (operator position Sound Pressure level)	Standby mode: <46 dB(A) Operating mode: <58 dB(A)
PC Configuration	Minimum: Pentium III, 1 GHz processor, 128 MB RAM Recommended: Pentium IV, 2.5 GHz processor, 512 MB RAM, USB 2.0
Supported Operating Systems	WINDOWS XP (supports USB 2.0) WINDOWS 2000 Professional (supports USB 2.0) WINDOWS Me (USB 1.1 support only) WINDOWS 98SE (USB 1.1 support only)
Approvals and Product Certifications	AS/NZS 3548 Class B (C-Tick Mark), CAN/CSA-C22.2 No. 60950 (C-UL Mark), Canada ICES-003 Issue 3 (Class B), GB4943, GB9254 (Class B), GB 17625.1 Harmonics (CCC "S&E" Mark), EN 55022 ITE Emissions (Class B), EN 61000-3-3 Flicker, EN 55024 ITE Immunity, (CE Mark), EN 60950 (TUV GS Mark), IEC 60950, CISPR 22 Class B, VCCI (Class B), CNS 13438 (Class B), (BSMI Mark), UL 60950 (UL Mark), CFR 47 Part 15 Subpart B (FCC Class B), Argentina S-Mark
Consumables Available	Feed Module, Roller Cleaning Pads, Staticide Wipes

Specifications are subject to change without notice. Throughput speeds may vary depending on your choice of driver, application software, operating system and PC.

For more information visit: www.kodak.com/go/docimaging



As an ENERGY STAR® Partner, Eastman Kodak Company has determined that these products meet ENERGY STAR® guidelines for energy efficiency.

- **Weight** i30: 3.6 kg
i40: 4.1 kg
- **Depth** 168 mm
- **Width** 337 mm
- **Height** 162 mm

(not including paper trays)



We're here for you.

Kodak Service & Support



Innovation you can count on™

© Eastman Kodak Company, 2005.
Kodak is a trademark of Eastman Kodak Company

Cat.No. 741 3297 DoldeMedien 0121_05

United Kingdom, Phone: +44 870 850 2351, Fax: +44 870 850 2352
Scandinavia, Phone: +45 701 57000, Fax: +45 701 57100
Germany, Austria and Switzerland, Phone: +49 711 406 2535, Fax: +49 711 406 3619
Eastern Europe, Middle East and Africa, Phone: +36 1 454 3031, Fax: +36 1 387 9113
France, Spain, Portugal, Phone: +33 1 4001 4082, fax +33 1 4001 3981
Italy, Phone: +39 0266028338, Fax: +39 0266028358
The Netherlands, Phone: +31 347 363 612, Fax: +31 347 363 606
Belgium and Luxembourg, Phone: +32 262 68506, Fax: +32 262 68502